



### What to expect after install...

Your 3M window film has been applied with a water/ soap mix. During install, all efforts have been made to remove this solution. There will still be a small amount of moisture retained between the glass and the film, this is normal, and can take up to 1 month (up to two months for Thinsulate) to dissipate through the film. As this moisture is drying, the finish may look patchy, this will clear up as the moisture dries.

Please refrain from disturbing the edges or any irregularities that may occur (this is also normal and they will resolve as the film dries) as the film is not fully adhered to the surface until all the moisture has gone.

### Recommended cleaning methods...

Cleaner used	Cleaning Method
Commercially available window cleaner (eg.Windex) & nonabrasive paper towel	Light wiping motion
Clean & dry lint free soft cloth e.g. microfiber cloth (see important note below)	Light wiping motion with a mist of water or cleaner
Commercially available window cleaner (eg.Windex) with window cleaning squeegee	Side to side. Ensure squeegee is free from dirt, nicks and any other contamination
Isopropyl Alcohol with nonabrasive paper towel	Light wiping motion

### Important Note...

DO NOT use knives, scrapers, brushes, abrasives etc to clean the film.  
DO NOT rub vigorously.  
DO NOT rub repeatedly in one area.  
DO NOT apply heavy pressure in any cleaning operation.

### General Care...

Do not affix tapes, suction cups, stickers, etc. to the film surface. Doing so will damage the surface of the film, and will void your product warranty.

Following these few simple instructions will ensure a long servicable life for your new film. Should the film be damaged in any way it can be removed and replaced without causing any harm to the underlying surface. Please call us on the below number should you have any queries or concerns and we will do our best to help.